



Standard Features

- A unique thermal break system resulting in reduced heat transfer and incidence of condensation at high humidity levels.
- High strength 6063-T6 aluminum prevents warping, twisting, and bowing.
- Engineered sill design sloped to ease water run off.
- Full perimeter double weather-strip reduces water and air infiltration.
- Two tandem Rollers will provide years of quiet and smooth operation.
- Standard powder coated durable handles, with surface mount locking system.
- Glass is fully tempered and 1" sealed unit with optional Low Emissivity Coated glass, Warm Edge Spacer, and Argon Gas.





7000-3T Series

(Three Track Thermally Broken Aluminum System)

The 7000-3T Series Aluminum thermally broken stacking door system provides a unique three track frame system to allow dual operation. This design allows for maximum openings, with (2) panels that slide to one end adjacent to the fixed panel. This door is offered in a 3 panel configuration of 12ft, or the expanded 6 panel bi-parting configuration up to 24ft wide. The frame is supplied with a unique combination of PVC and POLYURETHANE thermal breaks which reduces condensation build up, and glass panels are infused with a single run thermal break to maximize performance. The aluminum is offered in a baked enamel finish, or any anodizing option in a one or two color system. Each operable panel is supplied with dual tandem metal ball bearing rollers to provide ease of operation for many trouble free years. An independent screen system is available as an option, the slide clear screen retracts when not in use, allowing for enjoyment of a full view.



7000-3



Clear Glass

Bronze Tint

Grey V-groove Tint

3X5 Grills

Foot Lock

Prairie Grills

Door Guardian Lock

GEM Windows and Doors 1590 The Queensway, Toronto, ON M8Z 1V1 416-533-4331 info@gemwindows.com

you to choose from.